


## Scheda Dati

060P2MEAGR

Pulsantiera a due mani ergonomica, grigia, alluminio



## Caratteristiche

|                         |  |
|-------------------------|--|
| <b>Gamma</b>            | Dispositivi di comando a due mani                    |
| <b>Componente</b>       | Pulsantiera a due mani protetta ergonomica           |
| <b>Codice</b>           | 060P2MEAGR   |
| <b>Descrizione</b>      | Pulsantiera a due mani ergonomica, grigia, alluminio |
| <b>Colore</b>           | Grigio RAL7016                                       |
| <b>Peso</b>             | 2980,0   |
| <b>Tariffa doganale</b> | 85371098   |
| <b>GTIN</b>             | 8052878074555  |

## Dati tecnici

|  |   |
|--|---|
| <b>Approvals</b>                         | CE  |
| <b>Compliance with standards</b>         | IEC-ENC60947-1, IEC-EN60947-5-1                     |
| <b>Compliance with standards</b>         | IEC-EN60204-1, UNI EN ISO 13849-1, UNI EN ISO 13851 |
| <b>Operating temperatures</b>            | -40° ÷ +70°C  |
| <b>Protection degree</b>                 | IP66 - IP69 (IEC-EN60529)                           |
| <b>Protection against impact</b>         | IK10 (IEC-EN62262)                                  |
| <b>Manufacturing process</b>             | Shell gravity diecasting                            |
| <b>Enclosure material</b>                | Aluminum Al Si11 Cu2 (EN AC46100)                   |
| <b>Screw material</b>                    | Stainless steel AISI 304                            |
| <b>Wrist support material</b>            | Stainless steel AISI 304                            |
| <b>Black base material</b>               | Steel   |
| <b>Operators plate material</b>          | Painted steel - thickness 1.5mm                     |
| <b>Painting</b>                          | Polyester powder coating                            |
| <b>Rated insulation voltage</b>          | Ui 690V - Uimp 4KV (IEC-EN60947-1)                  |
| <b>Protection against electric shock</b> | Class I (IEC-EN61140)                               |
| <b>Pushbutton characteristics</b>        | See the single items 020PTAASRK-020PTF9MGR-020GE11  |
| <b>Safety accessory</b>                  | 060MCP2M - 2 hand simultaneous action controller    |
| <b>Accessories</b>                       | Sealing screws 060VCE                               |
| <b>Floor-mount telescopic stand</b>      | Articles 060STP2M OR 060STP2MA                      |
| <b>Warranty period</b>                   | 18 months   |

# Disegni tecnici

