

Scheda Dati

060P2MGRP

Pupitre de commande bimanuelle, protégé, avec boutons-poussoirs, gris, aluminium



Caratteristiche

Portée	Dispositifs de commande à deux mains
Componente	Pupitre de commande bimanuelle protégé avec BP
Code	060P2MGRP
Désignation des marchandises	Pupitre de commande bimanuelle, protégé, avec boutons-poussoirs, gris, aluminium
Couleur	Grigio RAL7016
Peso	4454,0
Tariffa doganale	85371098
GTIN	8052878067403

Dati tecnici

Approvals	CE
Compliance with standards	IEC-ENC60947-1, IEC-EN60947-5-1
Compliance with standards	IEC-EN60204-1, UNI EN ISO 13849-1, UNI EN ISO 13851
Operating temperatures	-40° ÷ +70°C
Protection degree	IP66 - IP69 (IEC-EN60529)
Protection against impact	IK10 (IEC-EN62262)
Manufacturing process	Shell gravity diecasting
Enclosure material	Aluminum Al Si11 Cu2 (EN AC46100)
Screw material	Stainless steel AISI 304
Wrist support material	Stainless steel AISI 304
Black base material	Steel
Operators plate material	Painted steel - thickness 1.5mm
Painting	Polyester powder coating
Rated insulation voltage	Ui 690V - Uimp 4KV (IEC-EN60947-1)
Protection against electric shock	Class I (IEC-EN61140)
Pushbutton characteristics	See the single items 020PTAASRK-020PTF9MGR-020GE11
Safety accessory	060MCP2M - 2 hand simultaneous action controller
Accessories	Sealing screws 060VCE
Floor-mount telescopic stand	Articles 060STP2M OR 060STP2MA
Warranty period	18 months

Disegni tecnici

