

## Scheda Dati

060PA11

Interrupitor de pedal, 2 posiciones, palanca seguridad, (1 microinterruptor), N.O.+N.C., aluminio, sin resguardo



## Caratteristiche

|                         |  |
|-------------------------|--|
| <b>Rango</b>            | Interrupitores con pedal   |
| <b>Componente</b>       | Interrupitor pedal de aluminio sin tapa  |
| <b>Código</b>           | 060PA11  |
| <b>Descripción</b>      | Interrupitor de pedal, 2 posiciones, palanca seguridad, (1 microinterruptor), N.O.+N.C., aluminio, sin resguardo |
| <b>Color</b>            | Grigio   |
| <b>Peso</b>             | 1232,0   |
| <b>Tariffa doganale</b> | 85365080   |
| <b>GTIN</b>             | 8052878051341  |

## Dati tecnici

|                                   |   |
|-----------------------------------|---|
| <b>Approvals</b>                  | CE  |
| <b>Compliance with standards</b>  | IEC-ENC60947-1, IEC-EN60947-5-1                   |
| <b>Operating temperatures</b>     | -25° ÷ +70°C                                      |
| <b>Protection degree</b>          | IP54 (IEC-EN60529)                                |
| <b>Mechanical durability</b>      | 10.000.000 Operations                             |
| <b>Housing material</b>           | Metal: Aluminum / Thermoplastic: PP Polypropylene |
| <b>Tightening torque</b>          | 0.8 ÷ 1.2Nm (7.1÷10.6 Lb-in)                      |
| <b>Cable entry</b>                | M20x1,5   |
| <b>Contact movement</b>           | Snap action contact                               |
| <b>NC contacts (all versions)</b> | Positive opening function (IEC-EN60947-5-1 ann.K) |
| <b>Rated thermal current</b>      | Ith 10A (IEC-EN60947-1)                           |
| <b>Rated insulation voltage</b>   | Ui 300V - Uimp 2.5KV (IEC-EN60947-1)              |
| <b>Electrical ratings</b>         | AC15-DC13 (IEC-EN60947-5-1) - A600-Q300 (UL 508)  |
| <b>AC Performances</b>            | AC 24V-10A, 120V-6A, 240V-3A, 600V-1.2A           |
| <b>DC Performances</b>            | DC 24V-2.5A, 120V-0.6A, 240V-0.3A                 |
| <b>Microswitch</b>                | 1NO - 1NC change over, snap action                |
| <b>Actuating force</b>            | 34N   |
| <b>Pedal operation</b>            | Momentary - spring return when released           |
| <b>Warranty period</b>            | 18 months   |

# Disegni tecnici

