


Scheda Dati

060PA11

Poljinkytkin, 2-asentoinen, turvavipu, (1 mikrokytkin),N.O.+N.C.,alumiini, ilman suojusta



Caratteristiche

Range	Polkimella toimivat katkaisimet
Componente	Alumiiniset poljinkytkimet ilman kantta
Code	060PA11
Kuvaus	Poljinkytkin, 2-asentoinen, turvavipu, (1 mikrokytkin),N.O.+N.C.,alumiini, ilman suojusta
Väriä	Grigio
Peso	1232,0
Tariffa doganale	85365080
GT	8052878051341

Dati tecnici

Approvals	CE
Compliance with standards	IEC-ENC60947-1, IEC-EN60947-5-1
Operating temperatures	-25° ÷ +70°C
Protection degree	IP54 (IEC-EN60529)
Mechanical durability	10.000.000 Operations
Housing material	Metal: Aluminum / Thermoplastic: PP Polypropylene
Tightening torque	0.8 ÷ 1.2Nm (7.1÷10.6 Lb-in)
Cable entry	M20x1,5
Contact movement	Snap action contact
NC contacts (all versions)	Positive opening function (IEC-EN60947-5-1 ann.K)
Rated thermal current	Ith 10A (IEC-EN60947-1)
Rated insulation voltage	Ui 300V - Uimp 2.5KV (IEC-EN60947-1)
Electrical ratings	AC15-DC13 (IEC-EN60947-5-1) - A600-Q300 (UL 508)
AC Performances	AC 24V-10A, 120V-6A, 240V-3A, 600V-1.2A
DC Performances	DC 24V-2.5A, 120V-0.6A, 240V-0.3A
Microswitch	1NO - 1NC change over, snap action
Actuating force	34N
Pedal operation	Momentary - spring return when released
Warranty period	18 months

Disegni tecnici

