

## Datablad

060PA11

Pedaalschakelaar, 2 posities, veiligheidshendel (1 microschakelaar), N.O.+N.C.,aluminium, zonder afscherming



## Kenmerken

<b>Bereik</b>	Pedaalschakelaar
<b>Component</b>	Pedaalschakelaars in aluminium zonder deksel
<b>Rubriek</b>	060PA11
<b>Omschrijving</b>	Pedaalschakelaar, 2 posities, veiligheidshendel (1 microschakelaar), N.O.+N.C.,aluminium, zonder afscherming
<b>Kleur</b>	Grigio
<b>Gewicht</b>	1232,0
<b>Douanetarief</b>	85365080
<b>GTIN</b>	8052878051341

## Technische gegevens

<b>Approvals</b>	CE
<b>Compliance with standards</b>	IEC-ENC60947-1, IEC-EN60947-5-1
<b>Operating temperatures</b>	-25° ÷ +70°C
<b>Protection degree</b>	IP54 (IEC-EN60529)
<b>Mechanical durability</b>	10.000.000 Operations
<b>Housing material</b>	Metal: Aluminum / Thermoplastic: PP Polypropylene
<b>Tightening torque</b>	0.6 ÷ 0.8Nm (5.3÷7.1 Lb-in)
<b>Cable entry</b>	M20x1,5
<b>Contact movement</b>	Snap action contact
<b>NC contacts (all versions)</b>	Positive opening function (IEC-EN60947-5-1 ann.K)
<b>Rated thermal current</b>	Ith 10A (IEC-EN60947-1)
<b>Rated insulation voltage</b>	Ui 300V - Uimp 2.5KV (IEC-EN60947-1)
<b>Electrical ratings</b>	AC15-DC13 (IEC-EN60947-5-1) - A600-Q300 (UL 508)
<b>AC Performances</b>	AC 24V-10A, 120V-6A, 240V-3A, 600V-1.2A
<b>DC Performances</b>	DC 24V-2.5A, 120V-0.6A, 240V-0.3A
<b>Microswitch</b>	1NO - 1NC change over, snap action
<b>Actuating force</b>	34N
<b>Pedal operation</b>	Momentary - spring return when released
<b>Warranty period</b>	18 months

# Technische tekeningen

