

## Scheda Dati

060PM4S1

Boîte à boutons pendante avec 4 boutons-poussoirs à 1 vitesse et bouton-poussoir d'arrêt d'urgence, 1 N.C.



## Caratteristiche

<b>Portée</b>	Boîtes à boutons pendantes
<b>Componente</b>	Boîte à boutons pendante avec 4 opérateurs + arrêt d'urgence
<b>Code</b>	060PM4S1
<b>Désignation des marchandises</b>	Boîte à boutons pendante avec 4 boutons-poussoirs à 1 vitesse et bouton-poussoir d'arrêt d'urgence, 1 N.C.
<b>Couleur</b>	Giallo
<b>Peso</b>	550,0
<b>Tariffa doganale</b>	8537109899
<b>GTIN</b>	8052878051518

## Dati tecnici

<b>Approvals</b>	CE
<b>Compliance with standards</b>	IEC-ENC60947-1, IEC-EN60947-5-1
<b>Operating temperatures</b>	-15° ÷ +80°C
<b>Protection degree</b>	IP65 (IEC-EN60529)
<b>Protection against impact</b>	IK07 (IEC-EN62262)
<b>Mechanical durability</b>	500.000 Operations
<b>Enclosure material</b>	ABS Acrylonitrile butadiene styrene
<b>Flexible cable pipe</b>	Suitable for cable D.8÷17mm
<b>Rated insulation voltage</b>	Ui 300V - Uimp 2.5KV (IEC-EN60947-1)
<b>Electrical ratings</b>	AC15: Ue 250V max AC, Ie 4A max, 1000VA
<b>Mechanical interlock</b>	yes, between opposite direction pushbuttons
<b>Warranty period</b>	18 months

## Disegni tecnici

