

Fiche technique

060PM6S1

Boîte à boutons pendante avec 6 boutons-poussoirs à 1 vitesse et bouton-poussoir d'arrêt d'urgence, 1 N.C.



Caractéristiques

Portée	Boîtes à boutons pendantes
Composant	Boîte à boutons pendante avec 6 opérateurs + arrêt d'urgence
Code	060PM6S1
Désignation des marchandises	Boîte à boutons pendante avec 6 boutons-poussoirs à 1 vitesse et bouton-poussoir d'arrêt d'urgence, 1 N.C.
Couleur	Giallo
Poids	860,0
Tarif douanier	8537109899
GTIN	8052878051600

Données techniques

Approvals	CE
Compliance with standards	IEC-ENC60947-1, IEC-EN60947-5-1
Operating temperatures	-15° ÷ +80°C
Protection degree	IP65 (IEC-EN60529)
Protection against impact	IK07 (IEC-EN62262)
Mechanical durability	500.000 Operations
Enclosure material	ABS Acrylonitrile butadiene styrene
Flexible cable pipe	Suitable for cable D.8÷17mm
Rated insulation voltage	Ui 300V - Uimp 2.5KV (IEC-EN60947-1)
Electrical ratings	AC15: Ue 250V max AC, Ie 4A max, 1000VA
Mechanical interlock	yes, between opposite direction pushbuttons
Warranty period	18 months

Dessins techniques

