

Datasheet

060PM8S1

Pendant push-button station with 8 1-speed push-buttons and emergency stop push-button, 1 N.C.



Features

| | |
|-----------------------|--|
| Range | Pendant push-button stations |
| components | Pendant push-button stations, 8 operators + emergency |
| Code | 060PM8S1 |
| Description | Pendant push-button station with 8 1-speed push-buttons and emergency stop push-button, 1 N.C. |
| Colour | Giallo |
| Weight - gr | 1070.0 |
| Customs Tariff | 8537109899 |
| GTIN | 8052878051648 |

Datasheet

| | |
|----------------------------------|---|
| Approvals | CE |
| Compliance with standards | IEC-ENC60947-1, IEC-EN60947-5-1 |
| Operating temperatures | -15° ÷ +80°C |
| Protection degree | IP65 (IEC-EN60529) |
| Protection against impact | IK07 (IEC-EN62262) |
| Mechanical durability | 500.000 Operations |
| Enclosure material | ABS Acrylonitrile butadiene styrene |
| Flexible cable pipe | Suitable for cable D.8÷17mm |
| Rated insulation voltage | Ui 300V - Uimp 2.5KV (IEC-EN60947-1) |
| Electrical ratings | AC15: Ue 250V max AC, Ie 4A max, 1000VA |
| Mechanical interlock | yes, between opposite direction pushbuttons |
| Warranty period | 18 months |

Technical drawings

