

Datablad

060PMG

Doos knoppenbord, geel, in thermoplastisch hars, aluminium plaat zonder gaten



Kenmerken

Bereik	Mobiel knoppenbord
Component	Doos knoppenbord in thermoplastisch hars
Rubriek	060PMG
Omschrijving	Doos knoppenbord, geel, in thermoplastisch hars, aluminium plaat zonder gaten
Kleur	Giallo
Gewicht	576,0
Douanetarief	85381000
GTIN	8052878051662

Technische gegevens

Approvals	CE
Compliance with standards	IEC-EN60529
Compliance with standards	IEC-ENC60947-1, IEC-EN60947-5-1
Operating temperatures	-25° ÷ +65°C
Protection degree	IP66 - IP69 (IEC-EN60529)
Protection against impact	IK07 (IEC-EN62262)
Shock resistance	50g duration=11ms (EN-IEC 60068-2-27)
Housing material	High impact grade thermoplastic polymer
Manufacturing process	Injection moulding
Gasket material	EPDM Foam + adhesive
Screw material	Stainless steel AISI 304
Front plate material	Anodized aluminium - Thickness 2mm
Front plate material	PMMA polymethylmethacrylate
Tightening torque	1 ÷ 2,5Nm (8.8÷22.1 Lb-in)
Flexible cable gland	M20x1.5 suitable for cable D.6÷12mm
Protection against electric shock	Class I (IEC-EN61140)
Handle with left / right knockouts	For 016P3Pxxx 3 position enabling safety switch
Warranty period	18 months

Technische tekeningen

