

Datablad

060PMG

Doos knoppenbord, geel, in thermoplastisch hars, aluminium plaat zonder gaten



Kenmerken

| | |
|---------------------|---|
| Bereik | Mobiel knoppenbord |
| Component | Doos knoppenbord in thermoplastisch hars |
| Rubriek | 060PMG |
| Omschrijving | Doos knoppenbord, geel, in thermoplastisch hars, aluminium plaat zonder gaten |
| Kleur | Giallo |
| Gewicht | 576,0 |
| Douanetarief | 85381000 |
| GTIN | 8052878051662 |

Technische gegevens

| | |
|---|---|
| Approvals | CE |
| Compliance with standards | IEC-EN60529 |
| Compliance with standards | IEC-ENC60947-1, IEC-EN60947-5-1 |
| Operating temperatures | -25° ÷ +65°C |
| Protection degree | IP66 - IP69 (IEC-EN60529) |
| Protection against impact | IK07 (IEC-EN62262) |
| Shock resistance | 50g duration=11ms (EN-IEC 60068-2-27) |
| Housing material | High impact grade thermoplastic polymer |
| Manufacturing process | Injection moulding |
| Gasket material | EPDM Foam + adhesive |
| Screw material | Stainless steel AISI 304 |
| Front plate material | Anodized aluminium - Thickness 2mm |
| Front plate material | PMMA polymethylmethacrylate |
| Tightening torque | 1 ÷ 2,5Nm (8.8÷22.1 Lb-in) |
| Flexible cable gland | M20x1.5 suitable for cable D.6÷12mm |
| Protection against electric shock | Class I (IEC-EN61140) |
| Handle with left / right knockouts | For 016P3Pxxx 3 position enabling safety switch |
| Warranty period | 18 months |

Technische tekeningen

