

Hoja de datos

060PMGR

Caja botonera, gris, en resina termoplástica con placa aluminio sin orificios



Características

Rango	Botonera móvil
Componente	Caja botonera en resina termoplástica
Código	060PMGR
Descripción	Caja botonera, gris, en resina termoplástica con placa aluminio sin orificios
Color	Grigio RAL7016
Peso	680,0
Arancel aduanero	85381000
GTIN	8052878051679

Datos técnicos

Approvals	CE
Compliance with standards	IEC-EN60529
Compliance with standards	IEC-ENC60947-1, IEC-EN60947-5-1
Operating temperatures	-25° ÷ +65°C
Protection degree	IP66 - IP69 (IEC-EN60529)
Protection against impact	IK07 (IEC-EN62262)
Shock resistance	50g duration=11ms (EN-IEC 60068-2-27)
Housing material	High impact grade thermoplastic polymer
Manufacturing process	Injection moulding
Gasket material	EPDM Foam + adhesive
Screw material	Stainless steel AISI 304
Front plate material	Anodized aluminium - Thickness 2mm
Front plate material	PMMA polymethylmethacrylate
Tightening torque	1 ÷ 2,5Nm (8.8÷22.1 Lb-in)
Flexible cable gland	M20x1.5 suitable for cable D.6÷12mm
Protection against electric shock	Class I (IEC-EN61140)
Handle with left / right knockouts	For 016P3Pxxx 3 position enabling safety switch
Warranty period	18 months

Dibujos técnicos

