

Scheda Dati

060PMGR

Boîtier de commande, gris, en résine thermoplastique avec plaque sans trous en aluminium



Caratteristiche

Portée	Boîtier de commande mobile
Componente	Boîtier de commande en résine thermoplastique
Code	060PMGR
Désignation des marchandises	Boîtier de commande, gris, en résine thermoplastique avec plaque sans trous en aluminium
Couleur	Grigio RAL7016
Peso	680,0
Tariffa doganale	85381000
GTIN	8052878051679

Dati tecnici

Approvals	CE
Compliance with standards	IEC-EN60529
Compliance with standards	IEC-ENC60947-1, IEC-EN60947-5-1
Operating temperatures	-25° ÷ +65°C
Protection degree	IP66 - IP69 (IEC-EN60529)
Protection against impact	IK07 (IEC-EN62262)
Shock resistance	50g duration=11ms (EN-IEC 60068-2-27)
Housing material	High impact grade thermoplastic polymer
Manufacturing process	Injection moulding
Gasket material	EPDM Foam + adhesive
Screw material	Stainless steel AISI 304
Front plate material	Anodized aluminium - Thickness 2mm
Front plate material	PMMA polymethylmethacrylate
Tightening torque	1 ÷ 2,5Nm (8.8÷22.1 Lb-in)
Flexible cable gland	M20x1.5 suitable for cable D.6÷12mm
Protection against electric shock	Class I (IEC-EN61140)
Handle with left / right knockouts	For 016P3Pxxx 3 position enabling safety switch
Warranty period	18 months

Disegni tecnici

