

Datablad

060PPLT11

Pedaalschakelaar, 2 posities, veiligheidshendel, (1 microschakelaar), N.O.+N.C., thermoplastisch



Kenmerken

Bereik	Pedaalschakelaar
Component	Thermoplastische pedaalschakelaars
Rubriek	060PPLT11
Omschrijving	Pedaalschakelaar, 2 posities, veiligheidshendel, (1 microschakelaar), N.O.+N.C., thermoplastisch
Kleur	Grigio
Gewicht	750,0
Douanetarief	85365080
GTIN	8052878051792

Technische gegevens

Approvals	CE
Compliance with standards	IEC-ENC60947-1, IEC-EN60947-5-1
Operating temperatures	-25° ÷ +70°C
Protection degree	IP54 (IEC-EN60529)
Mechanical durability	10.000.000 Operations
Housing material	Metal: Aluminum / Thermoplastic: PP Polypropylene
Tightening torque	0.6 ÷ 0.8Nm (5.3÷7.1 Lb-in)
Cable entry	M20x1,5
Contact movement	Snap action contact
NC contacts (all versions)	Positive opening function (IEC-EN60947-5-1 ann.K)
Rated thermal current	Ith 10A (IEC-EN60947-1)
Rated insulation voltage	Ui 300V - Uimp 2.5KV (IEC-EN60947-1)
Electrical ratings	AC15-DC13 (IEC-EN60947-5-1) - A600-Q300 (UL 508)
AC Performances	AC 24V-10A, 120V-6A, 240V-3A, 600V-1.2A
DC Performances	DC 24V-2.5A, 120V-0.6A, 240V-0.3A
Microswitch	1NO - 1NC change over, snap action
Actuating force	34N
Pedal operation	Momentary - spring return when released
Warranty period	18 months

Technische tekeningen

