

Datenblatt

060PT11

Fußschalter, 2 Positionen (1 Mikro), N.O.+N.C., Thermoplast, ohne Hülle



Merkmale

| | |
|------------------------|---|
| Baureihe | Fußschalter |
| Komponenten | Thermoplastische Fußschalter ohne Abdeckung |
| Artikel-Nr. | 060PT11 |
| Beschreibung | Fußschalter, 2 Positionen (1 Mikro), N.O.+N.C., Thermoplast, ohne Hülle |
| Farbe | Rosso |
| Gewicht - gr | 632,0 |
| Zolltarifnummer | 85365080 |
| GTIN | 8052878051884 |

Technische Daten

| | |
|-----------------------------------|---|
| Approvals | CE |
| Compliance with standards | IEC-ENC60947-1, IEC-EN60947-5-1 |
| Operating temperatures | -25° ÷ +70°C |
| Protection degree | IP54 (IEC-EN60529) |
| Mechanical durability | 10.000.000 Operations |
| Housing material | Metal: Aluminum / Thermoplastic: PP Polypropylene |
| Tightening torque | 0.6 ÷ 0.8Nm (5.3÷7.1 Lb-in) |
| Cable entry | M20x1,5 |
| Contact movement | Snap action contact |
| NC contacts (all versions) | Positive opening function (IEC-EN60947-5-1 ann.K) |
| Rated thermal current | Ith 10A (IEC-EN60947-1) |
| Rated insulation voltage | Ui 300V - Uimp 2.5KV (IEC-EN60947-1) |
| Electrical ratings | AC15-DC13 (IEC-EN60947-5-1) - A600-Q300 (UL 508) |
| AC Performances | AC 24V-10A, 120V-6A, 240V-3A, 600V-1.2A |
| DC Performances | DC 24V-2.5A, 120V-0.6A, 240V-0.3A |
| Microswitch | 1NO - 1NC change over, snap action |
| Actuating force | 34N |
| Pedal operation | Momentary - spring return when released |
| Warranty period | 18 months |

Technische Zeichnungen

