
Datasheet

060PT2MAA
Protected two-hand control Techno 90, orange, thermoplastic



Features

Range	Two-hand control devices
components	Protected two-hand control station in thermoplastic
Code	060PT2MAA
Description	Protected two-hand control Techno 90, orange, thermoplastic
Colour	Arancio RAL2011 / Grigio RAL7035
Weight - gr	1195.0
Customs Tariff	85371098
GTIN	8052878078522

Datasheet

Approvals	CE
Compliance with standards	IEC-EN60947-5-5
Compliance with standards	IEC-ENC60947-1, IEC-EN60947-5-1
Compliance with standards	IEC-EN60204-1,UNI EN ISO 13849-1,UNI EN ISO 13851
Operating temperatures	-35° ÷ +80°C
Protection degree	IP66 - IP69 (IEC-EN60529)
Protection against impact	IK08 (IEC-EN62262)
Enclosure material	PA Polyamide - glass fiber reinforced
Gasket material	TPE thermoplastic elastomer
Screw material	Stainless steel AISI 304
Screw type	HEX 3 slotted head - M4 thread
Enclosure thickness	3,5mm
Tightening torque	0.8 ÷ 1.2 Nm (7.1 ÷ 10.6 Lb-in)
Protection against electric shock	Class II (IEC-EN61140)
Combustion behaviour	HB (UL94)
Combustion behaviour	650°(IEC-EN60695-2-12)
Fitted for outdoor application	yes
Pushbutton characteristics	See items from family 020 / CMD&SIGN; SM2 Ø22
Warranty period	18 months

Technical drawings

