

Datablad

080C0505-3

Doos in polycarbonaat 50x52x35,5



Kenmerken

Bereik	Kasten 50x52/65 mm
Component	Polycarbonaat drukknopkast 50x52 mm
Rubriek	080C0505-3
Omschrijving	Doos in polycarbonaat 50x52x35,5
Kleur	Grigio RAL7035
Gewicht	35,0
Douanetarief	85381000
GTIN	8052878054144

Technische gegevens

Approvals	CE, UL (yellow lid models not included)
UL Approval	Item will be labelled only upon specific request
Compliance with standards	IEC-EN62208, UL508, CSA C22.2 No.14-13
Operating temperatures	-35° ÷ +80°C
Protection degree	IP66 - IP69 - TYPE 4, 4X (IEC-EN60529 - NEMA 250)
Protection against impact	IK08 (IEC-EN62262)
Enclosure material	PC Polycarbonate - glass fiber reinforced
Gasket material	Polyurethane foam
Screw material	Stainless steel AISI 304
Tightening torque	0.6 ÷ 0.8Nm (5.3÷7.1 Lb-in)
Protection against electric shock	Class II (IEC-EN61140)
Heavy metal-free	yes
PVC-free	yes
Silicon-free	yes
Combustion behaviour	5VA (UL50 - UL746C)
Combustion behaviour	V-2 (UL94)
Combustion behaviour	960°(IEC-EN60695-2-11)
Warranty period	18 months

Technische tekeningen

