

Datenblatt

080C0606-5GA

Bedienpult-Gehäuse aus Polycarbonat 65x65x57 mit rotem Pilztaster Ø 32, Drehentriegelung



Merkmale

| | |
|------------------------|--|
| Baureihe | NOT-AUS-Taster-Gehäuse 65x65 mm |
| Komponenten | Not-Aus-Taster Ø 32, Drehentriegelung, im Gehäuse |
| Artikel-Nr. | 080C0606-5GA |
| Beschreibung | Bedienpult-Gehäuse aus Polycarbonat 65x65x57 mit rotem Pilztaster Ø 32, Drehentriegelung |
| Farbe | Giallo RAL1003 / Grigio RAL7035 / Operatore rosso |
| Gewicht - gr | 145,0 |
| Zolltarifnummer | 85371098 |
| GTIN | 8052878054212 |

Technische Daten

| | |
|--|--|
| Approvals | CE |
| Compliance with standards | IEC-EN62208 |
| Operating temperatures | -30° ÷ +70°C |
| Protection degree | IP66 - IP69 - TYPE 4, 4X (IEC-EN60529 - NEMA 250) |
| Protection against impact | IK08 (IEC-EN62262) |
| Enclosure material | PC Polycarbonate - glass fiber reinforced |
| Gasket material | Polyurethane foam |
| Screw material | PA Black Polyamide - glass fiber reinforced |
| Tightening torque | 0.6 ÷ 0.8Nm (5.3÷7.1 Lb-in) |
| Protection against electric shock | Class II (IEC-EN61140) |
| Heavy metal-free | yes |
| PVC-free | yes |
| Silicon-free | yes |
| Halogen-free | yes |
| Combustion behaviour | 5VA (UL50 - UL746C) |
| Combustion behaviour | V-2 (UL94) |
| Combustion behaviour | 960°(IEC-EN60695-2-11) |
| Fitted for outdoor application | yes |
| Pushbutton selection | See 020 product range: 020 SM2 Command&Signalling; |

Warranty period

18 months

Technische Zeichnungen

