

Datasheet

080C0606-5GA

Polycarbonate push-button enclosure 65x65x57 with red mushroom push-button Ø 32, twist release



Features

Range	Emergency stop push-button enclosure 65x65 mm
components	Emergency push-button Ø 32, twist release, with enclosure
Code	080C0606-5GA
Description	Polycarbonate push-button enclosure 65x65x57 with red mushroom push-button Ø 32, twist release
Colour	Giallo RAL1003 / Grigio RAL7035 / Operatore rosso
Weight - gr	145.0
Customs Tariff	85371098
GTIN	8052878054212

Datasheet

Approvals	CE
Compliance with standards	IEC-EN62208
Operating temperatures	-30° ÷ +70°C
Protection degree	IP66 - IP69 - TYPE 4, 4X (IEC-EN60529 - NEMA 250)
Protection against impact	IK08 (IEC-EN62262)
Enclosure material	PC Polycarbonate - glass fiber reinforced
Gasket material	Polyurethane foam
Screw material	PA Black Polyamide - glass fiber reinforced
Tightening torque	0.6 ÷ 0.8Nm (5.3÷7.1 Lb-in)
Protection against electric shock	Class II (IEC-EN61140)
Heavy metal-free	yes
PVC-free	yes
Silicon-free	yes
Halogen-free	yes
Combustion behaviour	5VA (UL50 - UL746C)
Combustion behaviour	V-2 (UL94)
Combustion behaviour	960°(IEC-EN60695-2-11)
Fitted for outdoor application	yes
Pushbutton selection	See 020 product range: 020 SM2 Command&Signalling;

Warranty period

18 months

Technical drawings

