

Hoja de datos

080C0606-5GFA

Caja botonera en policarbonato 65x65x57 con pulsador rojo fungiforme Ø 40, desenganche rotación



Características

Rango	Cajas botoneras pulsador emergencia 65x65 mm
Componente	Pulsador de emergencia Ø 40, desenganche rotación, con caja
Código	080C0606-5GFA
Descripción	Caja botonera en policarbonato 65x65x57 con pulsador rojo fungiforme Ø 40, desenganche rotación
Color	Giallo RAL1003 / Grigio RAL7035 / Operatore rosso
Peso	146,0
Arancel aduanero	85365080
GTIN	8052878054311

Datos técnicos

Approvals	CE
Compliance with standards	IEC-EN62208
Operating temperatures	-30° ÷ +70°C
Protection degree	IP66 - IP69 - TYPE 4, 4X (IEC-EN60529 - NEMA 250)
Protection against impact	IK08 (IEC-EN62262)
Enclosure material	PC Polycarbonate - glass fiber reinforced
Gasket material	Polyurethane foam
Screw material	PA Black Polyamide - glass fiber reinforced
Tightening torque	0.6 ÷ 0.8Nm (5.3÷7.1 Lb-in)
Protection against electric shock	Class II (IEC-EN61140)
Heavy metal-free	yes
PVC-free	yes
Silicon-free	yes
Halogen-free	yes
Combustion behaviour	5VA (UL50 - UL746C)
Combustion behaviour	V-2 (UL94)
Combustion behaviour	960°(IEC-EN60695-2-11)
Fitted for outdoor application	yes
Pushbutton selection	See 020 product range: 020 SM2 Command&Signalling;

Warranty period

18 months

Dibujos técnicos

