

Fiche technique

080C0606-5GFA

Boîte à boutons polycarbonate 65x65x57 avec B.P. coup de poing, rouge Ø 40, déverrouillage par rotation



Caractéristiques

| | |
|-------------------------------------|---|
| Portée | Boîtes à boutons arrêt urgence 65x65 mm |
| Composant | B.P. d'urgence Ø 40, déverrouillage rotation, avec boîte |
| Code | 080C0606-5GFA |
| Désignation des marchandises | Boîte à boutons polycarbonate 65x65x57 avec B.P. coup de poing, rouge Ø 40, déverrouillage par rotation |
| Couleur | Giallo RAL1003 / Grigio RAL7035 / Operatore rosso |
| Poids | 146,0 |
| Tarif douanier | 85365080 |
| GTIN | 8052878054311 |

Données techniques

| | |
|--|--|
| Approvals | CE |
| Compliance with standards | IEC-EN62208 |
| Operating temperatures | -30° ÷ +70°C |
| Protection degree | IP66 - IP69 - TYPE 4, 4X (IEC-EN60529 - NEMA 250) |
| Protection against impact | IK08 (IEC-EN62262) |
| Enclosure material | PC Polycarbonate - glass fiber reinforced |
| Gasket material | Polyurethane foam |
| Screw material | PA Black Polyamide - glass fiber reinforced |
| Tightening torque | 0.6 ÷ 0.8Nm (5.3÷7.1 Lb-in) |
| Protection against electric shock | Class II (IEC-EN61140) |
| Heavy metal-free | yes |
| PVC-free | yes |
| Silicon-free | yes |
| Halogen-free | yes |
| Combustion behaviour | 5VA (UL50 - UL746C) |
| Combustion behaviour | V-2 (UL94) |
| Combustion behaviour | 960°(IEC-EN60695-2-11) |
| Fitted for outdoor application | yes |
| Pushbutton selection | See 020 product range: 020 SM2 Command&Signalling; |

Warranty period

18 months

Dessins techniques

