

Scheda Dati

080C0606-5GFA

Caixa botoeira em polycarbonato 65x65x57 com botão vermelho cogumelo Ø 40, desengate rotação



Caratteristiche

Gama	Caixas botoeiras parada emergência 65x65 mm
Componente	Botão de emergência Ø 40, desengate rotação, com caixa
Código	080C0606-5GFA
Descrição	Caixa botoeira em polycarbonato 65x65x57 com botão vermelho cogumelo Ø 40, desengate rotação
Cor	Giallo RAL1003 / Grigio RAL7035
Peso	146,0
Tariffa doganale	85365080
GTIN	8052878054311

Dati tecnici

Approvals	CE, UL (yellow lid models not included)
UL Approval	Item will be labelled only upon specific request
Compliance with standards	IEC-EN62208
Operating temperatures	-35° ÷ +80°C
Protection degree	IP66 - IP69 - TYPE 4, 4X (IEC-EN60529 - NEMA 250)
Protection against impact	IK08 (IEC-EN62262)
Enclosure material	PC Polycarbonate - glass fiber reinforced
Gasket material	Polyurethane foam
Screw material	PA Black Polyamide - glass fiber reinforced
Tightening torque	0.8 ÷ 1.2Nm (7.1÷10.6 Lb-in)
Protection against electric shock	Class II (IEC-EN61140)
Heavy metal-free	yes
PVC-free	yes
Silicon-free	yes
Halogen-free	yes
Combustion behaviour	5VA (UL50 - UL746C)
Combustion behaviour	V-2 (UL94)
Combustion behaviour	960°(IEC-EN60695-2-11)
Fitted for outdoor application	yes

Warranty period	18 months
-----------------	-----------

Disegni tecnici

