

## Scheda Dati

080C0606-5P1C

Scatola pulsantiera in policarbonato 65x65x57, 1 foro Ø 22



## Caratteristiche

|                         |                                                            |
|-------------------------|------------------------------------------------------------|
| <b>Gamma</b>            | Scatole pulsantiera 65x65 mm                               |
| <b>Componente</b>       | Coperchio con 1 foro Ø 22                                  |
| <b>Codice</b>           | 080C0606-5P1C                                              |
| <b>Descrizione</b>      | Scatola pulsantiera in policarbonato 65x65x57, 1 foro Ø 22 |
| <b>Colore</b>           | Grigio RAL7035                                             |
| <b>Peso</b>             | 85,0                                                       |
| <b>Tariffa doganale</b> | 85381000                                                   |
| <b>GTIN</b>             | 8052878054373                                              |

## Dati tecnici

|                                          |                                                   |
|------------------------------------------|---------------------------------------------------|
| <b>Approvals</b>                         | CE, EAC                                           |
| <b>Compliance with standards</b>         | IEC-EN62208                                       |
| <b>Operating temperatures</b>            | -35° ÷ +80°C                                      |
| <b>Protection degree</b>                 | IP66 - IP69 - TYPE 4, 4X (IEC-EN60529 - NEMA 250) |
| <b>Protection against impact</b>         | IK08 (IEC-EN62262)                                |
| <b>Enclosure material</b>                | PC Polycarbonate - glass fiber reinforced         |
| <b>Gasket material</b>                   | Polyurethane foam                                 |
| <b>Screw material</b>                    | PA Black Polyamide - glass fiber reinforced       |
| <b>Tightening torque</b>                 | 0.6 ÷ 0.8Nm (5.3÷7.1 Lb-in)                       |
| <b>Protection against electric shock</b> | Class II (IEC-EN61140)                            |
| <b>Heavy metal-free</b>                  | yes                                               |
| <b>PVC-free</b>                          | yes                                               |
| <b>Silicon-free</b>                      | yes                                               |
| <b>Halogen-free</b>                      | yes                                               |
| <b>Combustion behaviour</b>              | 5VA (UL50 - UL746C)                               |
| <b>Combustion behaviour</b>              | V-2 (UL94)                                        |
| <b>Combustion behaviour</b>              | 960°(IEC-EN60695-2-11)                            |
| <b>Fitted for outdoor application</b>    | yes                                               |
| <b>Warranty period</b>                   | 18 months                                         |

## Disegni tecnici

