

Scheda Dati

080C0606-5PV

Scatola pulsantiera in policarbonato 65x65x57, con pulsante con guardia, verde



Caratteristiche

| | |
|-------------------------|--|
| Gamma | Scatole pulsantiere complete 65x65/94 mm |
| Componente | Pulsante con guardia, verde, con scatola |
| Codice | 080C0606-5PV |
| Descrizione | Scatola pulsantiera in policarbonato 65x65x57, |
| Colore | Grigio RAL7035 |
| Peso | 130,0 |
| Tariffa doganale | 85371098 |
| GTIN | 8052878054403 |

Dati tecnici

| | |
|--|--|
| Approvals | CE |
| Compliance with standards | IEC-EN62208 |
| Operating temperatures | -30° ÷ +70°C |
| Protection degree | IP66 - IP69 - TYPE 4, 4X (IEC-EN60529 - NEMA 250) |
| Protection against impact | IK08 (IEC-EN62262) |
| Enclosure material | PC Polycarbonate - glass fiber reinforced |
| Gasket material | Polyurethane foam |
| Screw material | PA Black Polyamide - glass fiber reinforced |
| Tightening torque | 0.6 ÷ 0.8Nm (5.3÷7.1 Lb-in) |
| Protection against electric shock | Class II (IEC-EN61140) |
| Heavy metal-free | yes |
| PVC-free | yes |
| Silicon-free | yes |
| Halogen-free | yes |
| Combustion behaviour | 5VA (UL50 - UL746C) |
| Combustion behaviour | V-2 (UL94) |
| Combustion behaviour | 960°(IEC-EN60695-2-11) |
| Fitted for outdoor application | yes |
| Pushbutton selection | See 020 product range: 020 SM2 Command&Signalling; |
| Warranty period | 18 months |

Disegni tecnici

