

Scheda Dati

080C0606-5SC

Boîte à boutons polycarbonate 65x65x57 avec bouton tournant à clé à 2 positions



Caratteristiche

Portée	Boîtes à boutons complètes 65x65/94 mm
Componente	Bouton tournant à clé à 2 positions, avec boîte
Code	080C0606-5SC
Désignation des marchandises	Boîte à boutons polycarbonate 65x65x57 avec bouton tournant à clé à 2 positions
Couleur	Grigio RAL7035
Peso	194,0
Tariffa doganale	85371098
GTIN	8052878054410

Dati tecnici

Approvals	CE, UL (yellow lid models not included)
UL Approval	Item will be labelled only upon specific request
Compliance with standards	IEC-EN62208
Operating temperatures	-35° ÷ +80°C
Protection degree	IP66 - IP69 - TYPE 4, 4X (IEC-EN60529 - NEMA 250)
Protection against impact	IK08 (IEC-EN62262)
Enclosure material	PC Polycarbonate - glass fiber reinforced
Gasket material	Polyurethane foam
Screw material	PA Black Polyamide - glass fiber reinforced
Tightening torque	0.8 ÷ 1.2Nm (7.1÷10.6 Lb-in)
Protection against electric shock	Class II (IEC-EN61140)
Heavy metal-free	yes
PVC-free	yes
Silicon-free	yes
Halogen-free	yes
Combustion behaviour	5VA (UL50 - UL746C)
Combustion behaviour	V-2 (UL94)
Combustion behaviour	960°(IEC-EN60695-2-11)
Fitted for outdoor application	yes
Warranty period	18 months

Disegni tecnici

