

Fiche technique

080C0606-5SM

Boîte à boutons polycarbonate 65x65x57 avec bouton tournant à manette à 2 positions, noir



Caractéristiques

Portée	Boîtes à boutons complètes 65x65/94 mm
Composant	Bouton tournant à manette à 2 positions, noir, avec boîte
Code	080C0606-5SM
Désignation des marchandises	Boîte à boutons polycarbonate 65x65x57 avec bouton tournant à manette à 2 positions, noir
Couleur	Grigio RAL7035
Poids	135,0
Tarif douanier	85371098
GTIN	8052878054434

Données techniques

Approvals	CE
Compliance with standards	IEC-EN62208
Operating temperatures	-30° ÷ +70°C
Protection degree	IP66 - IP69 - TYPE 4, 4X (IEC-EN60529 - NEMA 250)
Protection against impact	IK08 (IEC-EN62262)
Enclosure material	PC Polycarbonate - glass fiber reinforced
Gasket material	Polyurethane foam
Screw material	PA Black Polyamide - glass fiber reinforced
Tightening torque	0.6 ÷ 0.8Nm (5.3÷7.1 Lb-in)
Protection against electric shock	Class II (IEC-EN61140)
Heavy metal-free	yes
PVC-free	yes
Silicon-free	yes
Halogen-free	yes
Combustion behaviour	5VA (UL50 - UL746C)
Combustion behaviour	V-2 (UL94)
Combustion behaviour	960°(IEC-EN60695-2-11)
Fitted for outdoor application	yes
Pushbutton selection	See 020 product range: 020 SM2 Command&Signalling;

Warranty period

18 months

Dessins techniques

