

Fiche technique

080C0606-5T

Boîte à boutons polycarbonate 65x65x57 couvercle transparent, sans trous



Caractéristiques

Portée	Boîtes à boutons 65x65 mm
Composant	Couvercle transparent, sans trous
Code	080C0606-5T
Désignation des marchandises	Boîte à boutons polycarbonate 65x65x57 couvercle transparent, sans trous
Couleur	Grigio RAL7035
Poids	90,0
Tarif douanier	85381000
GTIN	8052878054441

Données techniques

Approvals	CE, UL (yellow lid models not included)
UL Approval	Item will be labelled only upon specific request
Compliance with standards	IEC-EN62208
Operating temperatures	-35° ÷ +80°C
Protection degree	IP66 - IP69 - TYPE 4, 4X (IEC-EN60529 - NEMA 250)
Protection against impact	IK08 (IEC-EN62262)
Enclosure material	PC Polycarbonate - glass fiber reinforced
Gasket material	Polyurethane foam
Screw material	PA Black Polyamide - glass fiber reinforced
Tightening torque	0.6 ÷ 0.8Nm (5.3÷7.1 Lb-in)
Protection against electric shock	Class II (IEC-EN61140)
Heavy metal-free	yes
PVC-free	yes
Silicon-free	yes
Halogen-free	yes
Combustion behaviour	5VA (UL50 - UL746C)
Combustion behaviour	V-2 (UL94)
Combustion behaviour	960°(IEC-EN60695-2-11)
Fitted for outdoor application	yes
Warranty period	18 months

Dessins techniques

