

Datablad

080C0606-5T

Doos knoppenbord in polycarbonaat 65x65x57 transparant deksel, zonder gaten



Kenmerken

Bereik	Drukknopkasten 65x65 mm
Component	Transparant deksel zonder gaten
Rubriek	080C0606-5T
Omschrijving	Doos knoppenbord in polycarbonaat 65x65x57 transparant deksel, zonder gaten
Kleur	Grigio RAL7035
Gewicht	90,0
Douanetarief	85381000
GTIN	8052878054441

Technische gegevens

Approvals	CE, UL (yellow lid models not included)
UL Approval	Item will be labelled only upon specific request
Compliance with standards	IEC-EN62208
Operating temperatures	-35° ÷ +80°C
Protection degree	IP66 - IP69 - TYPE 4, 4X (IEC-EN60529 - NEMA 250)
Protection against impact	IK08 (IEC-EN62262)
Enclosure material	PC Polycarbonate - glass fiber reinforced
Gasket material	Polyurethane foam
Screw material	PA Black Polyamide - glass fiber reinforced
Tightening torque	0.6 ÷ 0.8Nm (5.3÷7.1 Lb-in)
Protection against electric shock	Class II (IEC-EN61140)
Heavy metal-free	yes
PVC-free	yes
Silicon-free	yes
Halogen-free	yes
Combustion behaviour	5VA (UL50 - UL746C)
Combustion behaviour	V-2 (UL94)
Combustion behaviour	960°(IEC-EN60695-2-11)
Fitted for outdoor application	yes
Warranty period	18 months

Technische tekeningen

