

Scheda Dati

080C0609-5S47

Polykarbonaatti painikepaneelikotelo 65x94x57 jossa kaksi mustaa painiketta suojuksella, nuolet



Caratteristiche

| | |
|-------------------------|---|
| Range | Täydelliset Painikekotelot 65x65/94 mm |
| Componente | 2 Painikkeet suojuksella, nuolet, kanssa kotelo |
| Code | 080C0609-5S47 |
| Kuvaus | Polykarbonaatti painikepaneelikotelo 65x94x57 jossa kaksi mustaa painiketta suojuksella, nuolet |
| Väriä | Grigio RAL7035 |
| Peso | 190,0 |
| Tariffa doganale | 85371098 |
| GT | 8052878054632 |

Dati tecnici

| | |
|--|---|
| Approvals | CE, UL (yellow lid models not included) |
| UL Approval | Item will be labelled only upon specific request |
| Compliance with standards | IEC-EN62208 |
| Operating temperatures | -35° ÷ +80°C |
| Protection degree | IP66 - IP69 - TYPE 4, 4X (IEC-EN60529 - NEMA 250) |
| Protection against impact | IK08 (IEC-EN62262) |
| Enclosure material | PC Polycarbonate - glass fiber reinforced |
| Gasket material | Polyurethane foam |
| Screw material | PA Black Polyamide - glass fiber reinforced |
| Tightening torque | 0.8 ÷ 1.2Nm (7.1÷10.6 Lb-in) |
| Protection against electric shock | Class II (IEC-EN61140) |
| Heavy metal-free | yes |
| PVC-free | yes |
| Silicon-free | yes |
| Halogen-free | yes |
| Combustion behaviour | 5VA (UL50 - UL746C) |
| Combustion behaviour | V-2 (UL94) |
| Combustion behaviour | 960°(IEC-EN60695-2-11) |
| Fitted for outdoor application | yes |

Warranty period

18 months

Disegni tecnici

