

## Scheda Dati

080C0909-5P2

Boîte à boutons polycarbonate 94x94x57, 2 trous Ø 22



## Caratteristiche

<b>Portée</b>	Boîtes à boutons 94x94 mm
<b>Componente</b>	Couvercle avec 2 trous Ø 22
<b>Code</b>	080C0909-5P2
<b>Désignation des marchandises</b>	Boîte à boutons polycarbonate 94x94x57, 2 trous Ø 22
<b>Couleur</b>	Grigio RAL7035
<b>Peso</b>	143,0
<b>Tariffa doganale</b>	85381000
<b>GTIN</b>	8052878054830

## Dati tecnici

<b>Approvals</b>	CE, UL (yellow lid models not included)
<b>UL Approval</b>	Item will be labelled only upon specific request
<b>Compliance with standards</b>	IEC-EN62208
<b>Operating temperatures</b>	-35° ÷ +80°C
<b>Protection degree</b>	IP66 - IP69 - TYPE 4, 4X (IEC-EN60529 - NEMA 250)
<b>Protection against impact</b>	IK08 (IEC-EN62262)
<b>Enclosure material</b>	PC Polycarbonate - glass fiber reinforced
<b>Gasket material</b>	Polyurethane foam
<b>Screw material</b>	PA Black Polyamide - glass fiber reinforced
<b>Tightening torque</b>	0.8 ÷ 1.2Nm (7.1÷10.6 Lb-in)
<b>Protection against electric shock</b>	Class II (IEC-EN61140)
<b>Heavy metal-free</b>	yes
<b>PVC-free</b>	yes
<b>Silicon-free</b>	yes
<b>Halogen-free</b>	yes
<b>Combustion behaviour</b>	5VA (UL50 - UL746C)
<b>Combustion behaviour</b>	V-2 (UL94)
<b>Combustion behaviour</b>	960°(IEC-EN60695-2-11)
<b>Fitted for outdoor application</b>	yes
<b>Warranty period</b>	18 months

## Disegni tecnici

