

## Scheda Dati

080C0909-8T

Polykarbonaatti painikepaneelikotelo 94x94x81, läpinäkyvä kansi ilman aukkoja



## Caratteristiche

Range	Painikekotelot 94x94 mm
Componente	Läpinäkyvä kansi ilman aukkoja
Code	080C0909-8T
Kuvaus	Polykarbonaatti painikepaneelikotelo 94x94x81, läpinäkyvä kansi ilman aukkoja
Väriä	Grigio RAL7035
Peso	196,0
Tariffa doganale	85381000
GT	8052878054946

## Dati tecnici

Approvals	CE, UL (yellow lid models not included)
UL Approval	Item will be labelled only upon specific request
Compliance with standards	IEC-EN62208
Operating temperatures	-35° ÷ +80°C
Protection degree	IP66 - IP69 - TYPE 4, 4X (IEC-EN60529 - NEMA 250)
Protection against impact	IK08 (IEC-EN62262)
Enclosure material	PC Polycarbonate - glass fiber reinforced
Gasket material	Polyurethane foam
Screw material	PA Black Polyamide - glass fiber reinforced
Tightening torque	0.8 ÷ 1.2Nm (7.1÷10.6 Lb-in)
Protection against electric shock	Class II (IEC-EN61140)
Heavy metal-free	yes
PVC-free	yes
Silicon-free	yes
Halogen-free	yes
Combustion behaviour	5VA (UL50 - UL746C)
Combustion behaviour	V-2 (UL94)
Combustion behaviour	960°(IEC-EN60695-2-11)
Fitted for outdoor application	yes
Warranty period	18 months

## Disegni tecnici

