

Scheda Dati

080C0913-8P2
Polykarbonaatti painikepaneelikotelo 94x130x81, 2 aukkoa Ø 22

Caratteristiche

Range	Painikekotelot 94x130 mm
Componente	Kansi 2 aukolla Ø 22
Code	080C0913-8P2
Kuvaus	Polykarbonaatti painikepaneelikotelo 94x130x81, 2 aukkoa Ø 22
Väriä	Grigio RAL7035
Peso	250,0
Tariffa doganale	85381000
GT	8052878055066

Dati tecnici

Approvals	CE, UL (yellow lid models not included)
UL Approval	Item will be labelled only upon specific request
Compliance with standards	IEC-EN62208
Operating temperatures	-35° ÷ +80°C
Protection degree	IP66 - IP69 - TYPE 4, 4X (IEC-EN60529 - NEMA 250)
Protection against impact	IK08 (IEC-EN62262)
Enclosure material	PC Polycarbonate - glass fiber reinforced
Gasket material	Polyurethane foam
Screw material	PA Black Polyamide - glass fiber reinforced
Tightening torque	0.8 ÷ 1.2Nm (7.1÷10.6 Lb-in)
Protection against electric shock	Class II (IEC-EN61140)
Heavy metal-free	yes
PVC-free	yes
Silicon-free	yes
Halogen-free	yes
Combustion behaviour	5VA (UL50 - UL746C)
Combustion behaviour	V-2 (UL94)
Combustion behaviour	960°(IEC-EN60695-2-11)
Fitted for outdoor application	yes
Warranty period	18 months

Disegni tecnici

