# Datasheet

## 080C0913-8S2
## Polycarbonate push-button enclosure 94x130x81, 2 holes Ø 30

## Features

| | |
|---|---|
| **Range** | Push-button enclosures 94x130 mm |
| **components** | 2-hole lid Ø 30 |
| **Code** | 080C0913-8S2 |
| **Description** | Polycarbonate push-button enclosure 94x130x81, 2 holes Ø 30 |
| **Colour** | Grigio RAL7035 |
| **Weight - gr** | 246.0 |
| **Customs Tariff** | 85381000 |
| **GTIN** | 8052878055103 |

## Datasheet

| | |
|---|---|
| **Approvals** | CE, EAC |
| **Compliance with standards** | IEC-EN62208 |
| **Operating temperatures** | -35° ÷ +80°C |
| **Protection degree** | IP66 - IP69 - TYPE 4, 4X (IEC-EN60529 - NEMA 250) |
| **Protection against impact** | IK08 (IEC-EN62262) |
| **Enclosure material** | PC Polycarbonate - glass fiber reinforced |
| **Gasket material** | Polyurethane foam |
| **Screw material** | PA Black Polyamide - glass fiber reinforced |
| **Tightening torque** | 0.6 ÷ 0.8Nm (5.3÷7.1 Lb-in) |
| **Protection against electric shock** | Class II (IEC-EN61140) |
| **Heavy metal-free** | yes |
| **PVC-free** | yes |
| **Silicon-free** | yes |
| **Halogen-free** | yes |
| **Combustion behaviour** | 5VA (UL50 - UL746C) |
| **Combustion behaviour** | V-2 (UL94) |
| **Combustion behaviour** | 960°(IEC-EN60695-2-11) |
| **Fitted for outdoor application** | yes |
| **Warranty period** | 18 months |

# Technical drawings