

## Scheda Dati

080C0918-8P5C

Caixa botoeira em polycarbonato 94x180x81, 5 furos Ø 22



## Caratteristiche

|                  |                                                         |
|------------------|---------------------------------------------------------|
| Gama             | Caixas botoeiras 94x180 mm                              |
| Componente       | Tampa com 5 furos Ø 22                                  |
| Código           | 080C0918-8P5C                                           |
| Descrição        | Caixa botoeira em polycarbonato 94x180x81, 5 furos Ø 22 |
| Cor              | Grigio RAL7035                                          |
| Peso             | 330,0                                                   |
| Tariffa doganale | 85381000                                                |
| GTIN             | 8052878055301                                           |

## Dati tecnici

|                                   |                                                   |
|-----------------------------------|---------------------------------------------------|
| Approvals                         | CE, UL (yellow lid models not included)           |
| UL Approval                       | Item will be labelled only upon specific request  |
| Compliance with standards         | IEC-EN62208                                       |
| Operating temperatures            | -35° ÷ +80°C                                      |
| Protection degree                 | IP66 - IP69 - TYPE 4, 4X (IEC-EN60529 - NEMA 250) |
| Protection against impact         | IK08 (IEC-EN62262)                                |
| Enclosure material                | PC Polycarbonate - glass fiber reinforced         |
| Gasket material                   | Polyurethane foam                                 |
| Screw material                    | PA Black Polyamide - glass fiber reinforced       |
| Tightening torque                 | 0.8 ÷ 1.2Nm (7.1÷10.6 Lb-in)                      |
| Protection against electric shock | Class II (IEC-EN61140)                            |
| Heavy metal-free                  | yes                                               |
| PVC-free                          | yes                                               |
| Silicon-free                      | yes                                               |
| Halogen-free                      | yes                                               |
| Combustion behaviour              | 5VA (UL50 - UL746C)                               |
| Combustion behaviour              | V-2 (UL94)                                        |
| Combustion behaviour              | 960°(IEC-EN60695-2-11)                            |
| Fitted for outdoor application    | yes                                               |
| Warranty period                   | 18 months                                         |

# Disegni tecnici

