

Datasheet

080C0918-8P6

Polycarbonate push-button enclosure 94x180x81, 6 holes Ø 22



Features

| | |
|-----------------------|---|
| Range | Push-button enclosures 94x180 mm |
| components | 6-hole lid Ø 22 |
| Code | 080C0918-8P6 |
| Description | Polycarbonate push-button enclosure 94x180x81, 6 holes Ø 22 |
| Colour | Grigio RAL7035 |
| Weight - gr | 302.0 |
| Customs Tariff | 85381000 |
| GTIN | 8052878055325 |

Datasheet

| | |
|--|---|
| Approvals | CE, EAC |
| Compliance with standards | IEC-EN62208 |
| Operating temperatures | -35° ÷ +80°C |
| Protection degree | IP66 - IP69 - TYPE 4, 4X (IEC-EN60529 - NEMA 250) |
| Protection against impact | IK08 (IEC-EN62262) |
| Enclosure material | PC Polycarbonate - glass fiber reinforced |
| Gasket material | Polyurethane foam |
| Screw material | PA Black Polyamide - glass fiber reinforced |
| Tightening torque | 0.6 ÷ 0.8Nm (5.3÷7.1 Lb-in) |
| Protection against electric shock | Class II (IEC-EN61140) |
| Heavy metal-free | yes |
| PVC-free | yes |
| Silicon-free | yes |
| Halogen-free | yes |
| Combustion behaviour | 5VA (UL50 - UL746C) |
| Combustion behaviour | V-2 (UL94) |
| Combustion behaviour | 960°(IEC-EN60695-2-11) |
| Fitted for outdoor application | yes |
| Warranty period | 18 months |

Technical drawings

