

## Datablad

080C0918-8T

Doos knoppenbord in polycarbonaat 94x180x81, transparant deksel, zonder gaten



## Kenmerken

|                     |   |
|---------------------|---|
| <b>Bereik</b>       | Drukknopkasten 94x180 mm  |
| <b>Component</b>    | Transparant deksel zonder gaten   |
| <b>Rubriek</b>      | 080C0918-8T   |
| <b>Omschrijving</b> | Doos knoppenbord in polycarbonaat 94x180x81, transparant deksel, zonder gaten |
| <b>Kleur</b>        | Grigio RAL7035  |
| <b>Gewicht</b>      | 300,0   |
| <b>Douanetarief</b> | 85381000  |
| <b>GTIN</b>         | 8052878055349   |

## Technische gegevens

|  |   |
|--|---|
| <b>Approvals</b>                         | CE, UL (yellow lid models not included)           |
| <b>UL Approval</b>                       | Item will be labelled only upon specific request  |
| <b>Compliance with standards</b>         | IEC-EN62208                                       |
| <b>Operating temperatures</b>            | -35° ÷ +80°C                                      |
| <b>Protection degree</b>                 | IP66 - IP69 - TYPE 4, 4X (IEC-EN60529 - NEMA 250) |
| <b>Protection against impact</b>         | IK08 (IEC-EN62262)                                |
| <b>Enclosure material</b>                | PC Polycarbonate - glass fiber reinforced         |
| <b>Gasket material</b>                   | Polyurethane foam                                 |
| <b>Screw material</b>                    | PA Black Polyamide - glass fiber reinforced       |
| <b>Tightening torque</b>                 | 0.6 ÷ 0.8Nm (5.3÷7.1 Lb-in)                       |
| <b>Protection against electric shock</b> | Class II (IEC-EN61140)                            |
| <b>Heavy metal-free</b>                  | yes   |
| <b>PVC-free</b>                          | yes   |
| <b>Silicon-free</b>                      | yes   |
| <b>Halogen-free</b>                      | yes   |
| <b>Combustion behaviour</b>              | 5VA (UL50 - UL746C)                               |
| <b>Combustion behaviour</b>              | V-2 (UL94)  |
| <b>Combustion behaviour</b>              | 960°(IEC-EN60695-2-11)                            |
| <b>Fitted for outdoor application</b>    | yes   |
| <b>Warranty period</b>                   | 18 months   |

## Technische tekeningen

---

