

Scheda Dati

080C1118-9P4C

Caixa botoeira em policarbonato 110x180x90, 4 furos Ø 22



Caratteristiche

| | |
|-------------------------|--|
| Gama | Caixas botoeiras 110x180 mm |
| Componente | Tampa com 4 furos Ø 22 |
| Código | 080C1118-9P4C |
| Descrição | Caixa botoeira em policarbonato 110x180x90, 4 furos Ø 22 |
| Cor | Grigio RAL7035 |
| Peso | 376,0 |
| Tariffa doganale | 85381000 |
| GTIN | 8052878055417 |

Dati tecnici

| | |
|--|---|
| Approvals | CE, UL (yellow lid models not included) |
| UL Approval | Item will be labelled only upon specific request |
| Compliance with standards | IEC-EN62208 |
| Operating temperatures | -35° ÷ +80°C |
| Protection degree | IP66 - IP69 - TYPE 4, 4X (IEC-EN60529 - NEMA 250) |
| Protection against impact | IK08 (IEC-EN62262) |
| Enclosure material | PC Polycarbonate - glass fiber reinforced |
| Gasket material | Polyurethane foam |
| Screw material | PA Black Polyamide - glass fiber reinforced |
| Tightening torque | 0.8 ÷ 1.2Nm (7.1÷10.6 Lb-in) |
| Protection against electric shock | Class II (IEC-EN61140) |
| Heavy metal-free | yes |
| PVC-free | yes |
| Silicon-free | yes |
| Halogen-free | yes |
| Combustion behaviour | 5VA (UL50 - UL746C) |
| Combustion behaviour | V-2 (UL94) |
| Combustion behaviour | 960°(IEC-EN60695-2-11) |
| Fitted for outdoor application | yes |
| Warranty period | 18 months |

Disegni tecnici

