

Datablad

080C1825-8T

Doos knoppenbord in polycarbonaat 180x254x84, transparant deksel, zonder gaten



Kenmerken

| | |
|---------------------|--|
| Bereik | Drukknopkasten 180x254 mm |
| Component | Transparant deksel zonder gaten |
| Rubriek | 080C1825-8T |
| Omschrijving | Doos knoppenbord in polycarbonaat 180x254x84, transparant deksel, zonder gaten |
| Kleur | Grigio RAL7035 |
| Gewicht | 640,0 |
| Douanetarief | 85381000 |
| GTIN | 8052878055813 |

Technische gegevens

| | |
|--|---|
| Approvals | CE, UL (yellow lid models not included) |
| UL Approval | Item will be labelled only upon specific request |
| Compliance with standards | IEC-EN62208 |
| Operating temperatures | -35° ÷ +80°C |
| Protection degree | IP66 - IP69 - TYPE 4, 4X (IEC-EN60529 - NEMA 250) |
| Protection against impact | IK08 (IEC-EN62262) |
| Enclosure material | PC Polycarbonate - glass fiber reinforced |
| Gasket material | Polyurethane foam |
| Screw material | PA Black Polyamide - glass fiber reinforced |
| Tightening torque | 0.6 ÷ 0.8Nm (5.3÷7.1 Lb-in) |
| Protection against electric shock | Class II (IEC-EN61140) |
| Heavy metal-free | yes |
| PVC-free | yes |
| Silicon-free | yes |
| Halogen-free | yes |
| Combustion behaviour | 5VA (UL50 - UL746C) |
| Combustion behaviour | V-2 (UL94) |
| Combustion behaviour | 960°(IEC-EN60695-2-11) |
| Fitted for outdoor application | yes |
| Warranty period | 18 months |

Technische tekeningen

