

## Scheda Dati

080CA0808-6GP1E

Painikepaneelikotelo 85x85x60, 1 aukko Ø 22, keltaisella suojalla



## Caratteristiche

<b>Range</b>	Painikekotelot 85 mm
<b>Componente</b>	Painikepaneelikotelo 85x85 mm suojuksella
<b>Code</b>	080CA0808-6GP1E
<b>Kuvaus</b>	Painikepaneelikotelo 85x85x60, 1 aukko Ø 22, keltaisella suojalla
<b>Väriä</b>	Giallo RAL1003 / Grigio RAL7035
<b>Peso</b>	112,0
<b>Tariffa doganale</b>	8538100090
<b>GT</b>	8052878056094

## Dati tecnici

<b>Approvals</b>	CE
<b>Compliance with standards</b>	IEC-EN62208
<b>Operating temperatures</b>	-25° ÷ +50°C
<b>Protection degree</b>	IP65 (IEC-EN60529)
<b>Protection against impact</b>	IK07 (IEC-EN62262)
<b>Enclosure material</b>	ABS Acrylonitrile butadiene styrene
<b>Gasket material</b>	Silicon rubber
<b>Screw material</b>	Zinc plated steel
<b>Tightening torque</b>	0.8 ÷ 1.2Nm (7.1÷10.6 Lb-in)
<b>Protection against electric shock</b>	Class II (IEC-EN61140)
<b>Warranty period</b>	18 months

# Disegni tecnici

