

Scheda Dati

080CS0606-5GA

Polystyreeni painikekotelo 65x65x57 hätä-/seis-painikkella Ø 32, punainen, avaus kiertämällä



Caratteristiche

Range	Painikekotelot Häätä-Seis 65x65 mm
Componente	Hätä-/seis painike Ø 32, avaus kiertämällä, kanssa kotelo
Code	080CS0606-5GA
Kuvaus	Polystyreeni painikekotelo 65x65x57 hätä-/seis-painikkella Ø 32, punainen, avaus kiertämällä
Väriä	Giallo RAL1003 / Grigio RAL7035
Peso	126,0
Tariffa doganale	85371098
GT	8052878056254

Dati tecnici

Approvals	CE
Compliance with standards	IEC-EN62208, CEI-EN6070-1, CEI-EN60670-22
Operating temperatures	-25° ÷ +40°C
Protection degree	IP66 - IP69 - TYPE 4, 4X (IEC-EN60529 - NEMA 250)
Protection against impact	IK07 (IEC-EN62262)
Enclosure material	PS Polystyrene
Gasket material	Polyurethane foam
Screw material	PA Black Polyamide - glass fiber reinforced
Tightening torque	0.8 ÷ 1.2Nm (7.1÷10.6 Lb-in)
Protection against electric shock	Class II (IEC-EN61140)
Heavy metal-free	yes
PVC-free	yes
Silicon-free	yes
Halogen-free	yes
Combustion behaviour	HB (UL94)
Combustion behaviour	650°(IEC-EN60695-2-11)
Fitted for outdoor application	No
Warranty period	18 months

Disegni tecnici

