

Fiche technique

080CS0606-5GFA

Boîte à boutons polystyrène 65x65x57 avec B.P. coup de poing, rouge Ø 40, déverrouillage par rotation



Caractéristiques

Portée	Boîtes à boutons arrêt urgence 65x65 mm
Composant	B.P. d'urgence Ø 40, déverrouillage rotation, avec boîte
Code	080CS0606-5GFA
Désignation des marchandises	Boîte à boutons polystyrène 65x65x57 avec B.P. coup de poing, rouge Ø 40, déverrouillage par rotation
Couleur	Giallo RAL1003 / Grigio RAL7035 / Operatore rosso
Poids	127,0
Tarif douanier	85371098
GTIN	8052878056285

Données techniques

Approvals	CE
Compliance with standards	IEC-EN62208, CEI-EN6070-1, CEI-EN60670-22
Operating temperatures	-25° ÷ +40°C
Protection degree	IP66 - IP69 - TYPE 4, 4X (IEC-EN60529 - NEMA 250)
Protection against impact	IK07 (IEC-EN62262)
Enclosure material	PS Polystyrene
Gasket material	Polyurethane foam
Screw material	PA Black Polyamide - glass fiber reinforced
Tightening torque	0.6 ÷ 0.8Nm (5.3÷7.1 Lb-in)
Protection against electric shock	Class II (IEC-EN61140)
Heavy metal-free	yes
PVC-free	yes
Silicon-free	yes
Halogen-free	yes
Combustion behaviour	HB (UL94)
Combustion behaviour	650°(IEC-EN60695-2-11)
Fitted for outdoor application	No
Warranty period	18 months

Dessins techniques

