

Datasheet

080CS0606-5PR

Polystyrene push-button enclosure 65x65x57 with red guarded push-button



Features

Range	Push-button enclosures 65x65/94 mm
components	Guarded push-button, red, with enclosure
Code	080CS0606-5PR
Description	Polystyrene push-button enclosure 65x65x57 with red guarded push-button
Colour	Grigio RAL7016 / RAL7035 / Operatore rosso
Weight - gr	117.0
Customs Tariff	85371098
GTIN	8052878056339

Datasheet

Approvals	CE
Compliance with standards	IEC-EN62208, CEI-EN6070-1, CEI-EN60670-22
Operating temperatures	-25° ÷ +40°C
Protection degree	IP66 - IP69 - TYPE 4, 4X (IEC-EN60529 - NEMA 250)
Protection against impact	IK07 (IEC-EN62262)
Enclosure material	PS Polystyrene
Gasket material	Polyurethane foam
Screw material	PA Black Polyamide - glass fiber reinforced
Tightening torque	0.6 ÷ 0.8Nm (5.3÷7.1 Lb-in)
Protection against electric shock	Class II (IEC-EN61140)
Heavy metal-free	yes
PVC-free	yes
Silicon-free	yes
Halogen-free	yes
Combustion behaviour	HB (UL94)
Combustion behaviour	650°(IEC-EN60695-2-11)
Fitted for outdoor application	No
Warranty period	18 months

Technical drawings

