

## Fiche technique

080CS0606-5SM

Boîte à boutons polystyrène 65x65x57 avec bouton tournant à manette à 2 positions, noir



## Caractéristiques

<b>Portée</b>	Boîtes à boutons complètes 65x65/94 mm
<b>Composant</b>	Bouton tournant à manette à 2 positions, noir, avec boîte
<b>Code</b>	080CS0606-5SM
<b>Désignation des marchandises</b>	Boîte à boutons polystyrène 65x65x57 avec bouton tournant à manette à 2 positions, noir
<b>Couleur</b>	Grigio RAL7016 / RAL7035 / Operatore nero
<b>Poids</b>	122,0
<b>Tarif douanier</b>	85371098
<b>GTIN</b>	8052878056360

## Données techniques

<b>Approvals</b>	CE
<b>Compliance with standards</b>	IEC-EN62208, CEI-EN6070-1, CEI-EN60670-22
<b>Operating temperatures</b>	-25° ÷ +40°C
<b>Protection degree</b>	IP66 - IP69 - TYPE 4, 4X (IEC-EN60529 - NEMA 250)
<b>Protection against impact</b>	IK07 (IEC-EN62262)
<b>Enclosure material</b>	PS Polystyrene
<b>Gasket material</b>	Polyurethane foam
<b>Screw material</b>	PA Black Polyamide - glass fiber reinforced
<b>Tightening torque</b>	0.6 ÷ 0.8Nm (5.3÷7.1 Lb-in)
<b>Protection against electric shock</b>	Class II (IEC-EN61140)
<b>Heavy metal-free</b>	yes
<b>PVC-free</b>	yes
<b>Silicon-free</b>	yes
<b>Halogen-free</b>	yes
<b>Combustion behaviour</b>	HB (UL94)
<b>Combustion behaviour</b>	650°(IEC-EN60695-2-11)
<b>Fitted for outdoor application</b>	No
<b>Warranty period</b>	18 months

## Dessins techniques

