

Datablad

080CS0609-5S47

Doos knoppenbord in polystyreen 65x94x57 met 2 zwarte drukknoppen met bescherming, pijlen



Kenmerken

| | |
|---------------------|---|
| Bereik | Complete Drukknopkasten 65x65/94 mm |
| Component | 2 Drukknoppen met bescherming, pijlen, met drukknopkast |
| Rubriek | 080CS0609-5S47 |
| Omschrijving | Doos knoppenbord in polystyreen 65x94x57 met 2 zwarte drukknoppen met bescherming, pijlen |
| Kleur | Grigio RAL7035 / Operatori nero-nero |
| Gewicht | 172,0 |
| Douanetarief | 85371098 |
| GTIN | 8052878056520 |

Technische gegevens

| | |
|--|---|
| Approvals | CE |
| Compliance with standards | IEC-EN62208, CEI-EN6070-1, CEI-EN60670-22 |
| Operating temperatures | -25° ÷ +40°C |
| Protection degree | IP66 - IP69 - TYPE 4, 4X (IEC-EN60529 - NEMA 250) |
| Protection against impact | IK07 (IEC-EN62262) |
| Enclosure material | PS Polystyrene |
| Gasket material | Polyurethane foam |
| Screw material | PA Black Polyamide - glass fiber reinforced |
| Tightening torque | 0.6 ÷ 0.8Nm (5.3÷7.1 Lb-in) |
| Protection against electric shock | Class II (IEC-EN61140) |
| Heavy metal-free | yes |
| PVC-free | yes |
| Silicon-free | yes |
| Halogen-free | yes |
| Combustion behaviour | HB (UL94) |
| Combustion behaviour | 650°(IEC-EN60695-2-11) |
| Fitted for outdoor application | No |
| Warranty period | 18 months |

Technische tekeningen

