

## Scheda Dati

080CS0909-5

Polystyreeni painikepaneelikotelo 94x94x57, ilman aukkoja



## Caratteristiche

<b>Range</b>	Painikekotelot 94x94 mm
<b>Componente</b>	Kansi ilman aukkoja
<b>Code</b>	080CS0909-5
<b>Kuvaus</b>	Polystyreeni painikepaneelikotelo 94x94x57, ilman aukkoja
<b>Väriä</b>	Grigio RAL7035
<b>Peso</b>	123,0
<b>Tariffa doganale</b>	85381000
<b>GT</b>	8052878056599

## Dati tecnici

<b>Approvals</b>	CE
<b>Compliance with standards</b>	IEC-EN62208, CEI-EN6070-1, CEI-EN60670-22
<b>Operating temperatures</b>	-25° ÷ +40°C
<b>Protection degree</b>	IP66 - IP69 - TYPE 4, 4X (IEC-EN60529 - NEMA 250)
<b>Protection against impact</b>	IK07 (IEC-EN62262)
<b>Enclosure material</b>	PS Polystyrene
<b>Gasket material</b>	Polyurethane foam
<b>Screw material</b>	PA Black Polyamide - glass fiber reinforced
<b>Tightening torque</b>	0.8 ÷ 1.2Nm (7.1÷10.6 Lb-in)
<b>Protection against electric shock</b>	Class II (IEC-EN61140)
<b>Heavy metal-free</b>	yes
<b>PVC-free</b>	yes
<b>Silicon-free</b>	yes
<b>Halogen-free</b>	yes
<b>Combustion behaviour</b>	HB (UL94)
<b>Combustion behaviour</b>	650°(IEC-EN60695-2-11)
<b>Fitted for outdoor application</b>	No
<b>Warranty period</b>	18 months

## Disegni tecnici

