

## Scheda Dati

080CS0909-8P2

Scatola pulsantiera in polistirene 94x94x81, 2 fori Ø 22



## Caratteristiche

|                         |                                                          |
|-------------------------|----------------------------------------------------------|
| <b>Gamma</b>            | Scatole pulsantiera 94x94 mm                             |
| <b>Componente</b>       | Coperchio con 2 fori Ø 22                                |
| <b>Codice</b>           | 080CS0909-8P2                                            |
| <b>Descrizione</b>      | Scatola pulsantiera in polistirene 94x94x81, 2 fori Ø 22 |
| <b>Colore</b>           | Grigio RAL7035                                           |
| <b>Peso</b>             | 166,0                                                    |
| <b>Tariffa doganale</b> | 85381000                                                 |
| <b>GTIN</b>             | 8052878056711                                            |

## Dati tecnici

|                                          |                                                   |
|------------------------------------------|---------------------------------------------------|
| <b>Approvals</b>                         | CE                                                |
| <b>Compliance with standards</b>         | IEC-EN62208, CEI-EN6070-1, CEI-EN60670-22         |
| <b>Operating temperatures</b>            | -25° ÷ +40°C                                      |
| <b>Protection degree</b>                 | IP66 - IP69 - TYPE 4, 4X (IEC-EN60529 - NEMA 250) |
| <b>Protection against impact</b>         | IK07 (IEC-EN62262)                                |
| <b>Enclosure material</b>                | PS Polystyrene                                    |
| <b>Gasket material</b>                   | Polyurethane foam                                 |
| <b>Screw material</b>                    | PA Black Polyamide - glass fiber reinforced       |
| <b>Tightening torque</b>                 | 0.8 ÷ 1.2Nm (7.1÷10.6 Lb-in)                      |
| <b>Protection against electric shock</b> | Class II (IEC-EN61140)                            |
| <b>Heavy metal-free</b>                  | yes                                               |
| <b>PVC-free</b>                          | yes                                               |
| <b>Silicon-free</b>                      | yes                                               |
| <b>Halogen-free</b>                      | yes                                               |
| <b>Combustion behaviour</b>              | HB (UL94)                                         |
| <b>Combustion behaviour</b>              | 650°(IEC-EN60695-2-11)                            |
| <b>Fitted for outdoor application</b>    | No                                                |
| <b>Warranty period</b>                   | 18 months                                         |

## Disegni tecnici

