# Scheda Dati

080CS0913-8G
Scatola pulsantiera in polistirene 94x130x81, senza fori, giallo



## Caratteristiche

| | |
|---|---|
| **Gamma** | Scatole pulsantiere 94x130 mm |
| **Componente** | Coperchio giallo senza fori |
| **Codice** | 080CS0913-8G |
| **Descrizione** | Scatola pulsantiera in polistirene 94x130x81, senza fori, |
| **Colore** | Giallo RAL1003 / Grigio RAL7035 |
| **Peso** | 152,0 |
| **Tariffa doganale** | 85381000 |
| **GTIN** | 8052878056834 |

## Dati tecnici

| | |
|---|---|
| **Approvals** | CE |
| **Compliance with standards** | IEC-EN62208, CEI-EN6070-1, CEI-EN60670-22 |
| **Operating temperatures** | -25° ÷ +40°C |
| **Protection degree** | IP66 - IP69 - TYPE 4, 4X (IEC-EN60529 - NEMA 250) |
| **Protection against impact** | IK07 (IEC-EN62262) |
| **Enclosure material** | PS Polystyrene |
| **Gasket material** | Polyurethane foam |
| **Screw material** | PA Black Polyamide - glass fiber reinforced |
| **Tightening torque** | 0.6 ÷ 0.8Nm (5.3÷7.1 Lb-in) |
| **Protection against electric shock** | Class II (IEC-EN61140) |
| **Heavy metal-free** | yes |
| **PVC-free** | yes |
| **Silicon-free** | yes |
| **Halogen-free** | yes |
| **Combustion behaviour** | HB (UL94) |
| **Combustion behaviour** | 650°(IEC-EN60695-2-12) |
| **Fitted for outdoor application** | No |
| **Warranty period** | 18 months |

## Disegni tecnici

