

## Fiche technique

080CS0918-5P3

Boîtier à boutons polystyrène 94x180x57, 3 trous Ø 22



## Caractéristiques

|                                     |   |
|-------------------------------------|---|
| <b>Portée</b>                       | Boîtiers à boutons 94x180 mm                          |
| <b>Composant</b>                    | Couvercle avec 3 trous Ø 22                           |
| <b>Code</b>                         | 080CS0918-5P3   |
| <b>Désignation des marchandises</b> | Boîtier à boutons polystyrène 94x180x57, 3 trous Ø 22 |
| <b>Couleur</b>                      | Grigio RAL7035  |
| <b>Poids</b>                        | 197,0   |
| <b>Tarif douanier</b>               | 85381000  |
| <b>GTIN</b>                         | 8052878056919   |

## Données techniques

|  |   |
|--|---|
| <b>Approvals</b>                         | CE  |
| <b>Compliance with standards</b>         | IEC-EN62208, CEI-EN6070-1, CEI-EN60670-22         |
| <b>Operating temperatures</b>            | -25° ÷ +40°C                                      |
| <b>Protection degree</b>                 | IP66 - IP69 - TYPE 4, 4X (IEC-EN60529 - NEMA 250) |
| <b>Protection against impact</b>         | IK07 (IEC-EN62262)                                |
| <b>Enclosure material</b>                | PS Polystyrene                                    |
| <b>Gasket material</b>                   | Polyurethane foam                                 |
| <b>Screw material</b>                    | PA Black Polyamide - glass fiber reinforced       |
| <b>Tightening torque</b>                 | 0.6 ÷ 0.8Nm (5.3÷7.1 Lb-in)                       |
| <b>Protection against electric shock</b> | Class II (IEC-EN61140)                            |
| <b>Heavy metal-free</b>                  | yes   |
| <b>PVC-free</b>                          | yes   |
| <b>Silicon-free</b>                      | yes   |
| <b>Halogen-free</b>                      | yes   |
| <b>Combustion behaviour</b>              | HB (UL94)   |
| <b>Combustion behaviour</b>              | 650°(IEC-EN60695-2-11)                            |
| <b>Fitted for outdoor application</b>    | No  |
| <b>Warranty period</b>                   | 18 months   |

## Dessins techniques

