

## Datasheet

080CS0918-8

Polystyrene push-button enclosure 94x180x81, undrilled



## Features

|                       |  |
|-----------------------|--|
| <b>Range</b>          | Push-button enclosures 94x180 mm                       |
| <b>components</b>     | Undrilled lid  |
| <b>Code</b>           | 080CS0918-8  |
| <b>Description</b>    | Polystyrene push-button enclosure 94x180x81, undrilled |
| <b>Colour</b>         | Grigio RAL7035   |
| <b>Weight - gr</b>    | 263.0  |
| <b>Customs Tariff</b> | 85381000   |
| <b>GTIN</b>           | 8052878056971  |

## Datasheet

|  |   |
|--|---|
| <b>Approvals</b>                         | CE  |
| <b>Compliance with standards</b>         | IEC-EN62208, CEI-EN6070-1, CEI-EN60670-22         |
| <b>Operating temperatures</b>            | -25° ÷ +40°C                                      |
| <b>Protection degree</b>                 | IP66 - IP69 - TYPE 4, 4X (IEC-EN60529 - NEMA 250) |
| <b>Protection against impact</b>         | IK07 (IEC-EN62262)                                |
| <b>Enclosure material</b>                | PS Polystyrene                                    |
| <b>Gasket material</b>                   | Polyurethane foam                                 |
| <b>Screw material</b>                    | PA Black Polyamide - glass fiber reinforced       |
| <b>Tightening torque</b>                 | 0.6 ÷ 0.8Nm (5.3÷7.1 Lb-in)                       |
| <b>Protection against electric shock</b> | Class II (IEC-EN61140)                            |
| <b>Heavy metal-free</b>                  | yes   |
| <b>PVC-free</b>                          | yes   |
| <b>Silicon-free</b>                      | yes   |
| <b>Halogen-free</b>                      | yes   |
| <b>Combustion behaviour</b>              | HB (UL94)   |
| <b>Combustion behaviour</b>              | 650°(IEC-EN60695-2-11)                            |
| <b>Fitted for outdoor application</b>    | No  |
| <b>Warranty period</b>                   | 18 months   |

## Technical drawings

---

