# Datasheet

080CS1825-11
Polystyrene push-button enclosure 180x254x111, undrilled



## Features

| | |
|---|---|
| **Range** | Push-button enclosures 180x254 mm |
| **components** | Undrilled lid |
| **Code** | 080CS1825-11 |
| **Description** | Polystyrene push-button enclosure 180x254x111, undrilled |
| **Colour** | Grigio RAL7035 |
| **Weight - gr** | 640.0 |
| **Customs Tariff** | 85381000 |
| **GTIN** | 8052878057336 |

## Datasheet

| | |
|---|---|
| **Approvals** | CE |
| **Compliance with standards** | IEC-EN62208, CEI-EN6070-1, CEI-EN60670-22 |
| **Operating temperatures** | -25° ÷ +40°C |
| **Protection degree** | IP66 - IP69 - TYPE 4, 4X (IEC-EN60529 - NEMA 250) |
| **Protection against impact** | IK07 (IEC-EN62262) |
| **Enclosure material** | PS Polystyrene |
| **Gasket material** | Polyurethane foam |
| **Screw material** | PA Black Polyamide - glass fiber reinforced |
| **Tightening torque** | 0.6 ÷ 0.8Nm (5.3÷7.1 Lb-in) |
| **Protection against electric shock** | Class II (IEC-EN61140) |
| **Heavy metal-free** | yes |
| **PVC-free** | yes |
| **Silicon-free** | yes |
| **Halogen-free** | yes |
| **Combustion behaviour** | HB (UL94) |
| **Combustion behaviour** | 650°(IEC-EN60695-2-12) |
| **Fitted for outdoor application** | No |
| **Warranty period** | 18 months |

## Technical drawings

