

Datasheet

080CS2536-11

Polystyrene push-button enclosure 254x361x111, undrilled



Features

| | |
|-----------------------|--|
| Range | Push-button enclosures 254x361 mm |
| components | Undrilled lid |
| Code | 080CS2536-11 |
| Description | Polystyrene push-button enclosure 254x361x111, undrilled |
| Colour | Grigio RAL7035 |
| Weight - gr | 1140.0 |
| Customs Tariff | 85381000 |
| GTIN | 8052878057442 |

Datasheet

| | |
|--|---|
| Approvals | CE |
| Compliance with standards | IEC-EN62208, CEI-EN6070-1, CEI-EN60670-22 |
| Operating temperatures | -25° ÷ +40°C |
| Protection degree | IP66 - IP69 - TYPE 4, 4X (IEC-EN60529 - NEMA 250) |
| Protection against impact | IK07 (IEC-EN62262) |
| Enclosure material | PS Polystyrene |
| Gasket material | Polyurethane foam |
| Screw material | PA Black Polyamide - glass fiber reinforced |
| Tightening torque | 0.6 ÷ 0.8Nm (5.3÷7.1 Lb-in) |
| Protection against electric shock | Class II (IEC-EN61140) |
| Heavy metal-free | yes |
| PVC-free | yes |
| Silicon-free | yes |
| Halogen-free | yes |
| Combustion behaviour | HB (UL94) |
| Combustion behaviour | 650°(IEC-EN60695-2-11) |
| Fitted for outdoor application | No |
| Warranty period | 18 months |

Technical drawings

